

Multi-Fiber Switch



Multi-fiber Switch paired with ROGUE

Features

- Stand-alone operation as well as pairing with other testers including OTDRs and OLTS
- 12-fiber switching capability
- Dual wavelength, single-mode or multimode
- Rechargeable battery with USB port charging/communication

Applications

- Converts a single port tester into a multi-fiber tester utilizing your existing OLTS, OTDR, and VFL test equipment
- Efficiently test 12-fiber links without disconnecting/reconnecting
- Bi-directional testing without moving cables
- Certify MPO links to industry standards including base 8 applications

The density demands of today’s networks are driving more demand for multi-fiber connectivity. As the adoption of multi-fiber connectors becomes more prevalent in data centers, the ability to test these types of connections accurately and quickly has become even more critical.

AFL’s Multi-Fiber Switch enables the testing of MPO/MTP®-terminated cables. The switch allows you to utilize a single piece of test equipment to verify some or all of the fibers in a multi-fiber connector in a single test, saving you both time and money.

AFL’s Multi-Fiber Switch is compatible with your AFL FlexScan FS200 and FS300 series OTDRs and ROGUE® OLTS Certification equipment. The switch can be manually configured or remotely controlled via USB from both FlexScan OTDRs and ROGUE OLTS.

Specifications^a

OPTICAL		
Wavelength	1310/1550 nm, SM dual-wavelength	850/1300 nm, MM dual-wavelength
Insertion Loss	2.8 dB typ. – 3.3 dB max.	1.8 dB typ. – 2.3 dB max.
Optical Return Loss (ORL)	50 dB min.	—
Fiber Length	4.4 ± 0.5 m	
Optical Length Uniformity	± 0.15 m	
GENERAL		
Power	Li-Ion battery or USB interface	
Battery Life	1000 hours continuous operation	
Weight	0.3 kg (0.66 lb)	
Dimensions	12.9 x 6.9 x 3.1 cm (5.1 x 2.7 x 1.2 in)	
Operating Temperature	-20 °C to +60 °C, 0 to 90 % RH (non-condensing)	
Storage Temperature	-20 °C to +70 °C, 0 to 90 % RH (non-condensing)	

Notes:

a. All specifications valid at 23 °C ±2 °C (73.4 °F ±3.6 °F) unless otherwise specified.

Multi-Fiber Switch

Ordering Information

DESCRIPTION	AFL NO.
Multi-fiber Switch, 12 fibers SM, APC-SC, MPO fiber ring (non-pinned), soft case	MFS-12-SM-ASC-FR
Multi-fiber Switch, 12 fibers SM, APC-SC, soft case	MFS-12-SM-ASC
Multi-fiber Switch, 12 fibers SM, UPC-SC, soft case	MFS-12-SM-USC
Multi-fiber Switch, 12 fibers MM, UPC-SC, soft case	MFS-12-MM-USC

ROGUE MFS Certification Add-on Kits

Each Multi-Fiber Switch Certification Add-on kit include (2) Multi-Fiber Switches, (2) 6 in. USB-USB mini cables, (2) key up / key down MPO-MPO mating adapters, (2) MFS carry holsters, (1) One-Click Cleaner MPO, (2) MFS kit carry cases, test cords and mating adapters (see table below).


ADD-ON KIT	CONTAINS (ea.)			AFL NO.
	12F MFS SWITCH	REFERENCE TEST CORDS		
		SC-SC, 0.3 (m)	12F MPO-MPO, 2 (m)	
SM, SC/UPC-MPO/APC	(2) SM, SC/UPC-MPO/APC	(2) SM	(2) SM, type A unpinned; (2) SM, type A pinned/unpinned; (1) SM, type B unpinned	MPO-SM-CERT-ADD
MM, SC/UPC-MPO/UPC	(2) MM, SC/UPC-MPO/UPC	(2) MM	(2) OM4, type A unpinned; (2) OM4, type A pinned/unpinned; (1) OM4, type B unpinned	MPO-MM-CERT-ADD

MFS Multi-Fiber Switch OTDR Add-on Kit

Single-mode and multimode Multi-Fiber Switches (MFS) are available to accelerate OTDR testing of MPO-connectorized, multi-fiber cables. OTDR MFS Add-on Kits include (1) MFS with MPO connector, (1) single-fiber Fiber Ring to connect OTDR to the switch, plus (1) MPO Fiber Ring.


CONTAINS (ea.)			AFL NO.
12F MFS SWITCH	FIBER RING	MPO FIBER RING	
MFS-12-SM-ASC, SM, SC/APC-MPO/APC pinned	SM, 150 m, SC-ASC or ASC-ASC (depending on OTDR connector)	12F, 61m, MPO/APC-unpinned to MPO; Select pinned or unpinned network MPO connector	MPO-SM-OTDR-ADD
MFS-12-MM-USC, MM, SC/UPC-MPO/UPC pinned	OM3/4/5-compatible, SC-SC, 150 m	12F, 61m, MPO-unpinned to MPO; Select pinned or unpinned network MPO connector	MPO-MM-OTDR-ADD

Recommended Products



ROGUE® OLTS Certifier

- Bi-directional testing on up to 2 fibers at once
- Pass/Fail certification to ISO/IEC/TIA/IEEE and custom test limits
- Automatic dual-wavelength identification (Wave ID)



FlexScan® FS300 (quad) and FS200 (single-mode) OTDRs

- SmartAuto® 1-button automated testing for fast results
- LinkMap® color-coded icons for easy troubleshooting
- Flexpress® mode (FS200) completes OTDR test in <5 seconds!
- Integrated Source, Power Meter and VFL

Qualifications

CATEGORY	REGULATION/STANDARD	QUALIFICATION
CE Marking	EU	Compliant to relevant EU Directives on health, safety, and environmental protection, and certified with CE marking
Safety	EN	Compliant to EN 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 55011 for EMC requirements for industrial, scientific and medical equipment
RoHS	EU	Compliant to EU regulations Directive 2011/65/EU (RoHS 2) and Directive 2015/863 (RoHS 3)

Contact Sales@AFLglobal.com to schedule a demonstration or learn how to buy.

Visit www.AFLglobal.com/Test to learn more about Multi-Fiber Switch.

International Sales and Service Contact Information available at www.AFLglobal.com/Test/Contacts