

QSFP28 DR Single Lambda

100G Ethernet DR Transceiver

DESCRIPTION

The QSFP28 Single Lambda transceiver is a 100 Gbit/s pluggable module for bi-directional serial optical data communications such as 100GBASE Ethernet. The transceiver operates with one PAM4 modulated signal at 1310 nm.

The module is fully compliant with QSFP28 related MSA standards described in SFF-8665 and Digital Diagnostic functions are available through an I2C interface. QSFP28 Single Lambda complies with IEEE 802.3 and 100Gbase-DR.

APPLICATIONS

- 100GBASE-DR

FEATURES

- Up to 500 m transmission on singlemode fiber (with FEC)
- Hot-Pluggable QSFP28 footprint
- Duplex LC Optical interface
- QSFP28 MSA compatible
- Digital Diagnostics Monitoring interface
- Single 3.3 V power supply
- Power dissipation < 4.5 W
- RoHS-6 compliant (lead-free)
- Case operating temperature: 0°C to 70°C



LASER SAFETY

This transceiver is a Class 1 laser product. It complies with IEC-60825 and FDA 21 CFR 1040.10 and 1040.11. The transceiver must be operated within the specified temperature and voltage limits. The optical ports of the module need to be terminated with an optical connector or a dust plug.

OPTICAL PARAMETERS

Part no.	SM/MM Fiber	Wavelength [nm]	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]
QSFP28-DR	SM	1310 nm	-2.5 to 4	-5.5 to 4	3

Optical power values are per channel

ORDERING INFORMATION

Part no.	Description
QSFP28-DR	QSFP28, 100GBASE-LR, Single Lambda CWDM, 500 m, 3dB, SM