

SFP-H10GB-CU

10G Copper Twinax SFP+ Family

INTRODUCTION

The Fiberworks SFP+ Copper Twinax Cable assemblies are high performance, cost effective I/O solutions for 10G Ethernet and 10G Fiber Channel applications. The transceiver modules achieve high port density, configurability and utilization at a very low cost and reduce power budget. The high speed cable assemblies meet and exceed Gigabit Ethernet and Fiber Channel industry standard requirement for performance and reliability.

APPLICATIONS

- Storage Area Networks
- Network Attached Storage
- Storage Servers
- Switch fabric I/O
- Data center cabling infrastructure
- High density connections between networking equipment

FEATURES

- Hot-pluggable SFP+ 20 PIN footprint
- Data rate up to 11.3Gbps
- Full support 1G/2G/4G/8G Fiber Channel applications
- 3.3V power supply
- Metal enclosure for lower EMI
- Power consumption less than 0,5W
- Compliant with MSA SFP+
- Built-in Digital Optics Monitoring (DOM)
- RoHS-6 compliant (lead-free)
- Operating Case Temperature: Standard -5°C to +70°C



Ordering Information

Part no:	Description/Application
SFP-H10GB-CU1M	SFP+, 10GB, Copper, DDM, 1m
SFP-H10GB-CU3M	SFP+, 10GB, Copper, DDM, 3m
SFP-H10GB-CU5M	SFP+, 10GB, Copper, DDM, 5m
SFP-H10GB-CU7M	SFP+, 10GB, Copper, DDM, 7m
SFP-H10GB-CU10M	SFP+, 10GB, Copper, DDM, 10m