

# BC-11 battery charger

## External charger for BU-11 batteries

Charge BU-11 batteries  
outside the splicer body

Compact size, fits into  
splicer carrying case

Powered by ADC-1430S  
T-71 AC/DC adaptor



SPECIFICATION	
APPLICABLE BATTERIES	BU-11 and BU-11S
CHARGE TIME BU-11	<4 hours from fully discharged state
AC SUPPLY	100-240V ac, 50/60Hz with Sumitomo ADC-1430S AC adaptor
ENVIRONMENT	Operating temp: 0°C to 40°C Humidity ≤95% non-condensing
STORAGE	-40°C to +80°C Humidity ≤95% non-condensing, (BC-11 only, excludes battery)
DIMENSIONS	141mm(w) x 60mm(d) x 36mm and 350g
CHARGE INDICATOR	Yes, LED indicates charging operation

ORDERING INFORMATION	
BC-11	Part number: TA015PD0055 - Does not include battery or AC adaptor
ADC-1430S	Part number: TA015PD0061 - includes AC power cord
AC SUPPLY	100-240V ac, 50/60Hz with Sumitomo ADC-1430S AC adaptor

Sumitomo Electric reserves the right to alter product specifications without notice E&OE

Sumitomo Electric Europe Ltd

[www.sumielectric.com](http://www.sumielectric.com)

[seel@sumielectric.com](mailto:seel@sumielectric.com)

Document part number TZA015DO0001-01

Document release date 2015-04-14

© Sumitomo Electric Europe Ltd